



HOME STAGING

WOOD **COVERING WOOD**





WOOD 06









WOOD 21



WOOD 17

INFORMATION

SUPPORT:	Vinyl
ADHESIVE:	Acrylic polymer
PROTECTOR:	.150 micron siliconised paper
THICKNESS:	210 - 230 microns
ASPECT:	Light wood
APPLICATION SIDE:	Indoor
RESISTANCE:	Optimale
STANDARDS:	EUROCLASSES
SUSTAINABILITY:	10 years

DIMENSIONS

By roll:



1,22 x

10 m 30 m 50 m

LIGHT WOOD

These imitation light wood coverings have a slightly grooved texture that gives them an even more realistic appearance.

This decorative covering is perfect for covering your doors, walls, counters, etc. Choose the style you prefer to suit the ambience you want to create.



Durability: 12 to 15 years for vertical applications in Central Europe.



Use: flat or curved surfaces



Maintenance: after 30 days with a standard cleaning solution (non-abrasive, ammonia-free, etc.). Do not use cleaning products that could scratch the surface.



Storage: 2 years from delivery. This film should be stored away from excessive humidity and sunlight, at a temperature below 38°C.

To meet the highest standards, we recommend that you do not mix films from different productions.



Method of application

Two-step interior application. Remove the protective liner from the adhesive and press directly onto the wall for 7 seconds. Apply externally by applying a solidifying varnish.

Production monitoring and standards

In order to constantly improve our products, we may modify colours and manufacturing processes without prior notice. Before applying our films, we recommend that users ensure that they are suitable for the intended use and comply with current standards.