HOME STAGING DATA SHEET

Réflectiv Window Film

HOME STAGING

WOOD
COVERING WOOD

WOOD 10

WOOD 35

WOOD 23

WOOD 25

WOOD 45

WOOD 04

INFORMATION

SUPPORT : ..... Vinyl
ADHESIVE : ..... Acrylic polymer
PROTECTOR : ..... 150 micron siliconised paper
THICKNESS : ..... 210 - 230 microns
ASPECT: ..... Light wood
APPLICATION SIDE : ..... Indoor
RESISTANCE : ..... Optimale
STANDARDS : ..... EUROCLASSES
SUSTAINABILITY : ..... 10 years

DIMENSIONS

By roll :

1,22 x | 10 m / 30 m / 50 m

LIGHT WOOD

These imitation light wood coverings have a slightly grooved texture that gives them an even more realistic appearance.
This decorative covering is perfect for covering your doors, walls, counters, etc. Choose the style you prefer to suit the ambience you want to create.

Durability : 12 to 15 years for vertical applications in Central Europe.

Use : flat or curved surfaces

Maintenance : after 30 days with a standard cleaning solution (non-abrasive, ammonia-free, etc.). Do not use cleaning products that could scratch the surface.

Storage : 2 years from delivery. This film should be stored away from excessive humidity and sunlight, at a temperature below 38°C.

To meet the highest standards, we recommend that you do not mix films from different productions.

EUROCLASSES B, S1, D0

Application Note
SCAN ME

Video of the pose
SCAN ME

Method of application
Two-step interior application. Remove the protective liner from the adhesive and press directly onto the wall for 7 seconds. Apply externally by applying a solidifying varnish.

Production monitoring and standards
In order to constantly improve our products, we may modify colours and manufacturing processes without prior notice. Before applying our films, we recommend that users ensure that they are suitable for the intended use and comply with current standards.

Showroom : 36 rue Réaumur, 75003 Paris.
Siège social : P.A. des petits carreaux - 2 avenue des Orangers 94380 Bonneuil sur Marne - FRANCE
+33 (0)143 99 00 22 - info@reflectiv.com - www.reflectiv.com