



HOME STAGING

WOOD 57 COVERING WOOD

INDOOR INSTALLATION



This imitation light wood covering has a slightly grooved texture that gives it an even more realistic look. This decorative covering will be perfect to cover your doors, your walls, your counters ...



Durability: 12 to 15 years for a vertical application in Central Europe.



Use: for all types of glass.



Maintenance : after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



Storage: 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

INFORMATION

SUPPORT :.....Vinyl
ADHESIVE :.....Acrylic polymer
PROTECTOR :.....Siliconized paper 160 microns
THICKNESS :.....210 - 230 microns
ASPECT:.....Old wood
APPLICATION SIDE :..... Internal
RESISTANCE :.....Optimal
NORMES :.....EUROCLASSES
SUSTAINABILITY :.....10 years

DIMENSIONS

By roll :

1,22 x
10 m
30 m
50 m



Cutting per linear meter



Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.